



# METAL CONTAINER, a.s.

Sovietskych hrdinov 113, 089 01 Svidník, Slowakei

TECHNICAL SPECIFICATION	COMBINED CONTAINER office/storage	PUR SANDWICH CONTAINER	ISOLATED OFFICE CONTAINER
DIMENSIONS	20' 6 058x2 438x2 591mm	20' 6 058x2 438x2591mm 15' 4 500x2 438x2591mm 10' 2 991x2 438x2591mm	
CONSTRUCTION FRAME	All-welded-profiled steel 4mm		
WALLS, ROOF	Profiled sheet 1,5mm	PUR SANDWICH PANEL 60mm	Profiled sheet 1,5mm
FLOOR	<b>Office</b> Plywood: 21mm Linoleum: 1,2mm  <b>Storage</b> Steel riffled sheet : 3/4mm	Plywood: 21mm Linoleum: 1,5mm	Plywood: 21mm Linoleum: 1,2mm
ISOLATION	<b>Office</b> <b>Walls:</b> Rock wool 50mm  <b>Floor:</b> Rock wool 100mm	<b>Walls, floor, roof:</b> PUR SANDWICH PANEL 60mm Heat transfer coefficient: 0,38 W/m <sup>2</sup> K	<b>Walls:</b> Rock wool 50mm <b>Floor:</b> Rock wool 100mm
EQUIPMENT STANDARD OF 20' CONTAINER	<b>Office</b> <b>Plastic window+ex. roller blind</b> 900x1200mm <b>Plastic door</b> 800x2000mm  <b>Storage</b> Container doors	<b>Plastic window + external roller blind</b> 900x1200mm <b>Plastic door</b> 800x2000mm	
ELECTRICAL INSTALLATION STANDARD OF 20' CONTAINER	<b>Office</b> -Room distributor -Circuit breaker 2xDXh16/1/C, 1xDXh 10/1/C -Light 1x36W -Socket 3x220V/16A -Switch -Residual current device  <b>Storage</b> -380V input/output -Light 1x36W -Switch -Socket 1x220V/16A	-380V input/output -Room distributor -Circuit breaker 2xDXh16/1/C, 1xDXh 10/1/C -Light 2x36W -Socket 3x220V/16A -Switch -Residual current device	
RAL IN BASIC PRICE	5010, 9002, 9010, 7035, 5005, 7001	9002, 9010	5010, 9002, 9010, 7035, 5005, 7001

**METAL CONTAINER, a.s.**

Ident. No: 36 703 958

Registered in Commercial Register of District Court Presov., Section: Sa, Insertion No: 10345/P