



Technical Description

8ft

DIMENSIONS for 8ft container

	OUTSIDE	INSIDE
Length (mm)	2438	2258
Width (mm)	2200	2090
Height (mm)	2250	2054
Door clearance (mm)	2080x1930	
Capacity	8,5 m3	
Stacking (empty containers)	4 pcs	

STRUCTURE

- Container Frame:** All-welded-profiled steel 2.5-3mm.
- Forklift Pockets:** Standard, 2.5-3 mm welded profiled steel, distance – centre: 900 mm.
- Corner fittings:** Welded corner fittings, thickness 6mm.
- Walls and Roof:** Vertically corrugated steel 1.2-1.5mm. Walls are equipped with passive air vents.
- Container Door:** 2-wing container door, made of corrugated steel with rubber gasket, safety flap and painted 2pcs locking bars.

FLOOR


- Floor types
- SB- steel riffled floor 3+1mm, painted
- HB- wooden floor, 25mm impregnated
- HBSp- laminated plywood floor 21mm

	Weight (kg)	Certified payload (kg)	Payload (kg/m2)	Manipulation Forklift/Crane (kg)
Steel (SB)	650	4157	770	4157
Wood (HB)	600	1877	345	1877
Plywood (HBSp)	600	1877	345	1877

COATING

- Surface Treatment:** Synthetic paint (zinc phosphate with alkyd resin), primer: 60 µm, top layer: 60 µm.
- Surface preparation:** ST3 Standard.
- RAL OUT:** 5010, 7035, 9010 or 9002. Other shades available for extra PRICE
- RAL IN:** 7035

CERTIFICATION (on request)

- ISO 9001: 2008, TÜV ISO 3834-2, Penetrant Testing level2, Visual Testing level2, Certificate 1090.
-  **TÜVRheinland®**
Precisely Right.

Storage containers are not certified as ISO Freight containers. Storage containers produced by Metal Container, a.s. are to be used solely for storage purposes and are not designed for shipping, therefore maximum storage payload is calculated when the container is on the ground. The containers shall be placed on hard and level surfaces. Manipulation with empty container only.



METAL CONTAINER, a.s.

Sovietskych hrdinov 629/113

089 01 Svidník

Slovak Republic

Tel.: +421/ 547180100

sales@metalcontainer.sk

www.metalcontainer.sk

